

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An assembly for a panel comprising:
 - (a) a housing, wherein said housing comprises a chamber having a first end and a second end, such that the first end is shaped for insertion into the panel and the second end comprises an aperture, and wherein the housing further comprises at least one guide for positioning the housing in the panel; and
 - (b) an insert that fits into the aperture on the second end of the housing and extends ~~extending~~ beyond the second end of the housing, wherein a ~~face~~ terminal end surface of the insert ~~extending beyond the second end of the housing~~ comprises a ~~rounded~~ convex surface.
2. (Canceled)
3. (Withdrawn) The assembly of claim 1, wherein the sliding panel comprises a door.
4. (Previously Amended) The assembly of claim 1, wherein the first end of the housing is positioned at a preset distance from the second end of the housing such that when the housing is inserted into the panel, the first end of the housing abuts at least a portion of the panel.

5. (Previously Amended) The assembly of claim 1, wherein the positioning guide extends from an external surface of the housing to abut a portion of the panel.
6. (Original) The assembly of claim 1, wherein the housing chamber is at least partly cylindrical in shape.
7. (Original) The assembly of claim 6, wherein the chamber comprises a cylinder having at least one planar surface.
8. (Original) The assembly of claim 6, wherein the positioning guide comprises a flat planar extension positioned around the outer circumference of the aperture on the second end of the housing.
9. (Original) The assembly of claim 8, wherein the planar extension comprises a lip that extends perpendicular to the length of the aperture.
10. (Previously Amended) The assembly of claim 6, wherein the positioning guide exerts an outward force from the housing to impinge on at least a portion of the panel.
11. (Withdrawn) The assembly of claim 10, further comprising a plurality of positioning guides spaced around the outer surface of the housing unit.

12. (Withdrawn) The assembly of claim 11, wherein the positioning guides comprise ridges such that once the housing is inserted in the sliding panel, the ridges engage the sliding panel to prevent the housing from being removed from the panel.

13. (Withdrawn) The assembly of claim 1, wherein the housing chamber is at least partly rectangular in shape.

14. (Withdrawn) The assembly of claim 13, wherein the positioning guide comprises at least one flat planar extension that is positioned on the first end of the housing and that extends perpendicular to the length of the aperture in the housing.

15. (Withdrawn) The assembly of claim 14, wherein the flat planar extension comprises an aperture for insertion of a fastening element.

16. (Withdrawn) The assembly of claim 13, wherein the positioning guide comprise at least one U-shaped arm that extends from the second end of the housing to impinge on at least a portion of the sliding panel.

17. (Withdrawn) The assembly of claim 16, wherein the at least one U-shaped arm abuts at least a portion of a track in which the sliding panel slides.

18. (Original) The assembly of claim 1, wherein the insert is cylindrical in shape.
19. (Original) The assembly of claim 1, wherein the aperture comprises a threaded surface.
20. (Original) The assembly of claim 19, wherein the insert comprises a threaded surface compatible with the threaded surface in the housing.
21. (Original) The assembly of claim 20, wherein the insert comprises an aperture in one end for threading the insert into the aperture.
22. (Original) The assembly of claim 1, wherein the material used to make the assembly comprises plastic.
23. (Currently Amended) An assembly for a panel comprising:
- (a) a housing, wherein the housing comprises a chamber comprising a first end and a second end, such that the first end is shaped for insertion into the panel and the second end comprises a threaded aperture, and wherein the housing further comprises at least one guide for positioning the housing in the panel; and
 - (b) a threaded cylindrical button that fits into the aperture on the second end of the housing extending and extends beyond the second end of the housing, wherein a face terminal

~~end surface~~ of the button ~~extending beyond the second end of the housing~~ comprises a ~~rounded surface~~ spherical shape.

24. (Previously Amended) The assembly of claim 23, wherein the positioning guide extends from an external surface of the housing to abut a portion of the panel.

25. (Original) The assembly of claim 23, wherein the positioning guide comprises a flat planar surface that extends from the housing in a direction that is perpendicular to the length of the aperture in the housing chamber.

26. (Previously Amended) The assembly of claim 23, wherein the positioning guide exerts an outward force from the housing to impinge on at least a portion of the panel.

27. (Withdrawn) The assembly of claim 23, wherein the positioning guide comprises at least one U-shaped arm that extends from the second end of the housing to impinge on at least a portion of the sliding panel.

28. (Previously Amended) An article of manufacture comprising a panel having at least one adjustable assembly supporting the panel at least partially within a track supporting the panel in a frame, wherein the adjustable assembly comprises:

(a) a housing comprising a chamber having a first end and a second end, such that the first end is shaped for insertion into the panel and the second end comprises an aperture, and further comprising at least one guide for positioning the housing in the panel;

(b) an insert that fits into the aperture on the second end of the housing extending beyond the second end of the housing and the panel, wherein the insert comprises a surface that abuts the track and supports the panel in the track; and

(c) means for adjusting a position of the panel with respect to the track.

29. (Previously Amended) The article of manufacture of claim 28, wherein the panel comprises a window.

30. (Withdrawn) The article of manufacture of claim 28, wherein the sliding panel comprises a door.

31. (Previously Amended) The article of manufacture of claim 28, wherein the first end of the housing is positioned at a preset distance from the second end of the housing such that when the housing is inserted into the panel, the first end of the housing abuts at least a portion of the panel.

32. (Previously Amended) The article of manufacture of claim 28, wherein the positioning guide extends from an external surface of the housing to abut a portion of the panel.

33. (Original) The article of manufacture of claim 28, wherein the positioning guide comprises a flat planar surface that extends from the housing in a direction that is perpendicular to the length of the housing body.

34. (Previously Amended) The article of manufacture of claim 28, wherein the positioning guide exerts an outward force from the housing to impinge on at least a portion of the panel.

35. (Withdrawn) The article of manufacture of claim 28, wherein the positioning guide comprises at least one U-shaped arm that extends from the second end of the housing to impinge on at least a portion of the sliding panel.

36. (Original) The article of manufacture of claim 28, where the insert is cylindrical in shape.

37. (Previously Amended) The article of manufacture of claim 28, wherein the adjusting means comprises a threaded surface in the housing.

38. (Previously Amended) The article of manufacture of claim 37, wherein the adjusting means further comprises a threaded surface on the insert compatible with the threaded surface in the housing.

39-40. (Canceled)

Express Mail Label No. EV 783 700 872 US

Application No. 10/759,593

Attorney Docket No. 49942-296293

41. (Currently Amended) The article of manufacture of claim 28, ~~wherein a face of the insert~~
~~extending beyond the second end of the housing comprises a rounded surface~~ further
comprising means for re-adjusting the position of the panel with respect to the track after the
panel is installed in the track.